

FLOOR CARE



OFFENSE™

Patented, Fast Acting, No Rinse Stripper

- **Quickly Penetrates**
- **Low Odor & Low Foam**
- **No Rinse Required**



OFFENSE™

Patented, Fast Acting, No Rinse Stripper

OFFENSE™ quickly penetrates through floor finish buildup and suspends the stripped finish for rinse free removal. Low foam and low odor. Safe on most resilient and non-resilient floors that include mineral surfaces, terrazzo, concrete, vinyl, vinyl composition, asphalt, rubber, terrazzo, brick and quarry tile. Do not use on linoleum or tile that are in poor condition.

No Rinse or Neutralizing:

Rinsing is not required. Pick up the dissolved finish completely with a wet vac, mop or autoscrubber.

Machine Scrubbing Not Required:

The powerful solvent action of **OFFENSE™** dissolves finish buildup using only mop agitation.

Safer to Use:

Works with cool water for increased worker safety.

Time Saver:

OFFENSE™ will reduce the time and labor required to strip floors by 40% as compared to current conventional strippers.

USE INFORMATION:

Before stripping, always dust mop the floor and remove gum, labels and other attached soil deposits with long handled scraper or putty knife. **OFFENSE™** can be used on vinyl, vinyl composition, vinyl asbestos, asphalt, marble, terrazzo, concrete and magnesite floors. Always use "CAUTION" signs.

PRODUCT SPECIFICATIONS:

pH.....	13.0 ± .3
Color.....	Liquid, Clear to Colorless
Fragrance.....	Solvent
Freezing Point.....	About 32°F
Solubility in Water.....	Complete
Flash Point.....	None to Boiling

INGREDIENTS:

Water.....	7732-18-5
Ethylene glycol phenyl ether.....	122-99-6
Monoethanolamine.....	141-43-5
2-Butoxyethanol.....	111-76-2
Sodium 1-octane sulfonate.....	5324-84-5

DIRECTIONS FOR USE:

MOP ON - MOP OFF

1. **MIX** Dilute at 21 ounces per gallon (1:6 ratio) of cool water for normal buildup or 32 ounces per gallon (1:4 ratio) of cool water for extreme build up.
2. **MOP** the diluted solution of **OFFENSE™** onto the floor. Let stand for 4-5 minutes, then agitate with the same mop. Do not allow solution to dry.
3. **REMOVE** the remaining solution off the floor using a mop or wet vacuum. For best results use a rotary machine and black pad. Do not let solution dry.
4. **REPEAT** steps two and three if any finish remains on floor. Rinsing may be required for dilutions stronger than 1:4.

SPECIAL PRECAUTIONS: Use caution as floors become very slippery. Must be diluted. Not for use on wood or painted surfaces. Not for use on linoleum or rubber floors or daily maintenance of resilient floors. Before use on asphalt tile, test a small hidden area for any color change.

PRODUCT AVAILABILITY:

F218022.....	4/1 Gal.
F218026.....	1/5 Pail
F218038.....	1/55 Drum

Franklin Cleaning Technology

One Fuller Way
Great Bend, KS 67530
United States
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com

F2180SS-0318