

FLOOR CARE



Green Option™

Floor Stripper

- **Powerful, Economical Formula**
- **Low Odor & Low Foam**
- **Environmentally Preferred**



FRANKLIN
CLEANING TECHNOLOGY

Green Option™

Floor Stripper

Green Option™ Floor Stripper is a concentrated, low odor, non-butyl environmentally preferable stripper. It quickly penetrates and emulsifies built up layers of floor finish for efficient removal by autoscrubber or rotary machine. Green Option™ Floor Stripper is formulated specifically for removal of Green Option™ Floor Sealer/Finish as part of a complete environmentally preferable floor care program. Low foaming.

Economical:

Concentrated formula provides the power to effectively strip normal amounts of finishes and sealers.

Fast Acting:

Unique blend of active ingredients and surfactants quickly penetrate soil, sealers, finishes and waxes for quick emulsification and easy removal.

Low Odor:

Formulation does not contain offensive odors normally associated with traditional stripping formulas.

Safer to Use:

Green Option™ Floor Stripper meets the specific performance requirements for easy removal of Green Option™ Floor Sealer/Finish with a safer and environmentally responsible formula.

USE INFORMATION:

For use on vinyl, vinyl composition, asbestos, terrazzo, ceramic and quarry tile floors. For rubber and asphalt floors, test on a small inconspicuous area for compatibility. **DO NOT** use on linoleum, tile in poor condition, wood or painted surfaces.

PRODUCT SPECIFICATIONS:

pH.....	10.5 ± 0.5
Color.....	Clear
Physical State.....	Concentrated Liquid
Freezing Point.....	About 32°F
Solubility in Water.....	Complete
Flash Point.....	167°F

INGREDIENTS:

Water.....	7732-18-5
Dipropylene glycol monomethyl ether.....	34590-94-8
Benzyl alcohol.....	100-51-6
Dipropylene glycol n-butyl ether.....	29911-28-2
Sodium xylene sulfonate.....	1300-72-7
Monoethanolamine.....	141-43-5
Undeceth-7.....	34398-01-1

DIRECTIONS FOR USE FLOOR STRIPPING

1. **DILUTE** at 16 ounces per gallon (1:8 ratio) of cold water for normal stripping. 32 ounces per gallon (1:4 ratio) of cold water for heavy stripping.
2. **APPLY** the diluted solution of **GREEN OPTION™** Floor Stripper onto the floor with a FullPro mop.
3. **WAIT:** Let stand for 4-5 minutes, then agitate with the same mop. For best results use a rotary machine and black pad. Do not let solution dry.
4. **REMOVE** the solution from the floor using a mop or wet dry vacuum. For best results rinse the floor with clean water and a clean mop.
5. **REPEAT** steps two to four if any finish remains on floor.

SPECIAL PRECAUTIONS: Not for use on linoleum, tile in poor condition, wood or painted surfaces or for daily maintenance of resilient tile floors. Before use on asphalt tile or rubber, test a small hidden area for any color change.

PRODUCT AVAILABILITY:

F219025..... 1/5 Cube

Franklin Cleaning Technology

One Fuller Way
Great Bend, KS 67530
United States
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com

F2190SS-0318