


FRANKLIN
 CLEANING TECHNOLOGY


FILM BUSTER™

Baseboard Stripper

**FOR REMOVING SOIL
AND WAX BUILDUP
FROM BASEBOARDS
AND FLOORS**

DANGER

CONTENTS UNDER PRESSURE. CAUSES SEVERE
SKIN BURNS AND EYE DAMAGE.

See back panel for additional safety information.

NET WT. 18 oz. (510 g)

FILM BUSTER™ BASEBOARD STRIPPER

Film Buster Baseboard Stripper is a concentrated heavy duty cleaning formulation designed to remove floor finish, wax and soil build-up from baseboards, floor edges, corners and other difficult to reach areas. Use **Film Buster Baseboard Stripper** on vinyl/composition, asbestos, terrazzo, ceramic or quarry tiles. Pretest in an inconspicuous area for other surfaces. Do not use on painted surfaces or carpet.

DIRECTIONS:

1. Shake can well.
2. Hold can 6" to 8" from surface. Spray while holding can in an inverted position. Remove overspray.
3. Wait 5 minutes or longer if build-up is severe.
4. Scrub with abrasive pad or brush.
5. Rinse surface thoroughly with warm water.

DANGER

Contains gas under pressure; may explode if heated. Causes severe skin burns and eye damage. Causes serious eye damage. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Prevention

Keep away from heat / sparks / open flames / hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves / protective clothing / eye protection / face protection.

Response

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center / doctor. Specific treatment (see SDS). Wash contaminated clothing before reuse.

Storage

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

Disposal

Dispose of contents / container in accordance with local / regional / national / international regulations.

KEEP OUT OF REACH OF CHILDREN



Ingredients: Water (7732-18-5), Isopropanol (67-63-0), Isobutane (75-28-5), Diisopropanolamine (110-97-4), Potassium hydroxide (1310-58-3), Sodium metasilicate (6834-92-0).

Franklin Cleaning Technology

One Fuller Way
Great Bend, KS 67530
United States
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com



F424015-0515