

3v6™

Hard Floor Coating Formulated with VSP™ Technology

PRODUCT DESCRIPTION:

3v6™ Hard Floor Coating formulated with VSP™ Technology provides increased initial gloss and dramatically extended life with fewer coats of product on the floor. VSP™ proprietary coatings more effectively penetrate pores in floor substrates providing a smooth, glass-like and ultra-durable film, which dramatically reduces soil embedding and retention. Your floors will stay cleaner longer. As a result of the enhanced durability of 3v6™, strip cycles can be extended to 24-36 months without sacrificing appearance by following the recommended procedures.

FEATURES:

Brilliant Initial Gloss:

Due to the smooth, glass-like film surface of 3v6™, the initial gloss and depth of gloss is improved compared to traditional floor finishes. You get instant, visible and improved results on your floor.

Reduced Coats/Reduced Costs:

3v6™ performs better and lasts longer than traditional floor finishes with fewer coats applied. Cost savings in labor and materials are measurable.

Superior Soil Resistance:

Enhanced VSP™ Technology more effectively penetrates pores in floor substrates providing a smoother, high-gloss and more durable film, which dramatically reduces soil embedding and retention. Your floors will stay cleaner longer.

Extended Life Cycle:

3v6™ incorporates a proprietary formula that includes nano-ceramic particles to provide long-term resistance to scratching and abrasions as well as increased ability to withstand detergent scrubbing. Strip cycles can be extended to 24-36 months without sacrificing appearance when following the recommended procedures. Your labor and material costs are reduced.

PRODUCT SPECIFICATIONS:

pH.....	7.85-8.70
Appearance.....	Off White Emulsion
Fragrance.....	Acrylic
Freezing Point.....	About 32°F
Boiling Point.....	212°F
% Non-Volatile Solids.....	22 ± 0.5
% Total Solids.....	28.0
Solubility in Water.....	Dispersible
Flash Point.....	None
Coverage.....	1800 to 3000 sq. ft. per gallon
(may vary due to differences in porosity of the surface)	

INGREDIENTS:

Water.....	7732-18-5
Acrylic polymer.....	Mixture
Diethylene glycol monoethyl ether.....	111-90-0
Tri-butoxyethyl phosphate.....	78-51-3
2,2,4-trimethyl-1,3-pentanediol diisobutyrate.....	6846-50-0

PRODUCT AVAILABILITY:

- 9601.....4/1 gal.
- 9605.....1/5 gal. pail
- 96055.....1/55 gal. drum

END-USE-RATING



0	1	2	3	4
Minimal	Slight	Moderate	Serious	Severe
Minimo	Minimo	Moderar	Grave	Drastico

3v6™ Hard Floor Coating

3v6™ is a high-solids floor coating for High-Speed and Ultra-High Speed maintenance programs. 3v6™ can be used on all resilient floors and for sealed wood, cork, terrazzo and concrete floors.



DIRECTIONS FOR USE:

INITIAL APPLICATION

1. **REMOVE** old sealer/finish using a Fullpro stripper and following label directions.
2. **APPLY** a medium coat of 3v6™ using a clean finish mop.
3. **DRY:** Allow 20-30 minutes drying time. **
4. **APPLY** 3-4 coats for best results allowing for adequate drying time between each coat.

MAINTENANCE

1. **DUST MOP**, damp mop and sweep as needed.
 2. **AUTOSCRUB** or damp mop daily using NuShine UHS Cleaner / Restorer following label instructions.
 3. **BURNISH** using a light pad at least once per week.
 4. As needed, thoroughly scrub, rinse and recoat worn areas with 3v6™ to maintain the foundation or base.
- ** Due to differences in temperature and humidity, actual drying time may vary.

SLIP RESISTANCE: Static coefficient of friction (James Machine) meets or exceeds 0.5 as determined by ASTM Method D2047-82.

Warning: May cause eye and skin irritation.

Precautionary Statement

Prevention

Direct contact with eyes may cause temporary irritation. Prolonged skin contact may cause temporary irritation. Observe good industrial hygiene practices.

Response

Wash hands after handling.

Storage

Store away from incompatible materials.

Disposal

Dispose of waste and residues in accordance with local authority requirements.

KEEP OUT OF REACH OF CHILDREN

PERSONAL PROTECTION:

Respiratory Protection: Not needed under normal conditions.

Ventilation: Use with adequate ventilation.

Eye Protection: Safety glasses are recommended.

Protective Gloves: Protective gloves are optional.

Other Protective Clothing or Equipment: Wear clothing as necessary to prevent skin contact.

TRANSPORTATION INFORMATION:

U.S. DOT - Proper Shipping Name: Not regulated by DOT.

Marine Pollutant: No

© FULLER COMMERCIAL PRODUCTS - 2014

One Fuller Way
Great Bend, KS 67530
United States
www.fullercommercial.com

Customer Service (800) 848-4901
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 Hour Emergency (800) 424-9300

960TDS-0714