



# Appearance®

## Floor Finish

**FULLPRO**  
FULLER PROFESSIONAL

# Appearance®

## Floor Finish

**Appearance®** is a new generation floor finish that achieves maximum performance when maintained by spray buffing and/or high speed buffing. This versatile product provides outstanding response to a variety of equipment/speed/pad combinations to produce excellent results.

### Produces “Wet Look”:

Used in conjunction with a high speed buffer or burnisher, produces glossy, “wet look” floor. Does not powder. Long wearing.

### Unique Formulation:

Combination of polymers and synthetic waxes.

### Easy to Maintain:

Superior resistance to scuffing, scratching, and marking. Spray buffing will clean, repair and improve the beauty of the floor.

### UL Approved for Slip Resistance:

Resistance: Provides a safe, slip resistant surface.

## USE INFORMATION:

**Appearance® Floor Finish** is recommended for use in spray buffing or high speed buffing maintenance programs, on all resilient flooring, tile, terrazzo and clay tile. Not recommended for use on wood floors.

## PRODUCT SPECIFICATIONS:

|                            |   |
|----------------------------|---|
| pH.....                    | 8.6 ± 0.4   |
| Appearance.....            | Off White Emulsion  |
| Fragrance.....             | Acrylic   |
| Freezing Point.....        | About 32°F  |
| % Non-Volatile Solids..... | 18.5  |
| % Total Solids.....        | 23.5  |
| Boiling Point.....         | 212°F   |
| Solubility in Water.....   | Dispersible   |
| Flash Point.....           | None  |
| Coverage.....              | 1800 to 2200 sq. ft. per gallon<br>(may vary due to differences in porosity of the surface) |

## INGREDIENTS:

|  |            |
|--|------------|
| Water.....                             | 7732-18-5  |
| Styrene acrylate polymer.....          | 25085-34-1 |
| Diethylene glycol monoethyl ether..... | 111-90-0   |
| Ethylene copolymer.....                | 67892-91-5 |
| Tri-butoxyethyl phosphate.....         | 78-51-3    |
| Styrene acrylic copolymer.....         | Mixture    |

## DIRECTIONS FOR USE:

### INITIAL APPLICATION

1. **REMOVE** old sealer/finish using a Fullpro stripper and following label directions.
2. **APPLY** a thin coat of **Appearance®** using a clean finish mop.
3. **DRY:** Allow 20-30 minutes drying time.
4. **APPLY** 4 coats for best results allowing for adequate drying time between each coat.

### MAINTENANCE

1. **DUST MOP**, damp mop or sweep regularly. Use a neutral cleaner, such as Concur™.
2. For best results, **ALLOW Appearance®** to cure for 24 hours before buffing.
3. **SPRAY** buff as needed using high speed machine and appropriate pad.

**Note:** Clean and recoat areas as the foundation becomes thin or as buffing response decreases.

## PRODUCT AVAILABILITY:

|            |                |
|------------|----------------|
| 9631.....  | 4/1 Gal.       |
| 9635.....  | 1/5 Gal. Pail  |
| 96355..... | 1/55 Gal. Drum |

## Fuller Commercial Products

One Fuller Way  
Great Bend, KS 67530  
United States  
CHEMTREC (800) 424-9300  
Emergency (620) 792-1711  
24 hour Emergency (800) 424-9300  
www.fullercommercial.com

963SS-0418