

FULLPRO

FULLER PROFESSIONAL

APPEARANCE® ADMIRE™ Sealer



WARNING

See right panel for precautions and first aid.

Net Contents: 55 Gallons (208L)

APPEARANCE® ADMIRE™ Sealer

Product No.: 98655

APPEARANCE® ADMIRE™ Sealer urethane fortified formula provides the protection of a high quality sealer. APPEARANCE® ADMIRE™ Sealer is easy to apply, highly resistant to scuffing and to many solvents and chemicals. Can be used on terrazzo, quarry tile, brick, unglazed ceramic, Mexican tile, slate, unpolished marble and all types of resilient flooring.

INITIAL APPLICATION



CAUTION



1. REMOVE



2. APPLY



3. DRY



4. APPLY



1. DUST MOP



2. MOP

DIRECTIONS FOR FLOOR CLEANING

Always dust mop floor first. Remove gum, labels and other attached soil deposits with a putty knife or long handled scraper.

INITIAL APPLICATION

1. **REMOVE** old sealer/finish following label directions using an appropriate Fullpro stripper.
2. **APPLY** a thin coat of APPEARANCE® ADMIRE™ using a clean finish mop.
3. **DRY:** Allow 30-60 minutes drying time.
4. **APPLY** 3-4 additional coats. For best results allow adequate drying time between coats.

MAINTENANCE

1. **DUST MOP** the floor. Remove gum, labels and other attached soils with a long handled scraper or putty knife.
2. **DAMP MOP OR AUTOSCRUB** using a Fullpro cleaner, following the label directions.

Slip Resistance: Static coefficient of friction (James Machine) meets or exceeds 0.5 as determined by ASTM Method D2047-82.

FOR INDUSTRIAL USE ONLY

IMPORTANT: Use only as directed. Do not mix with anything unless recommended since harmful conditions and poor performance could result. Do not pour unused product back into original container. All floors are slippery when wet. To prevent falls, exercise care when working and block off traffic with "Caution" signs until floor is completely dry.

WARNING

May cause mild eye and skin irritation. Harmful to aquatic life.

Prevention

Avoid release to the environment.

Response

Wash hands after handling.

Storage

Store away from incompatible materials.

Disposal

Dispose of contents/container in accordance with local / regional / national / international regulations.

KEEP OUT OF REACH OF CHILDREN

INGREDIENTS/INGREDIENTES

	CAS#
Water/Agua	7732-18-5
Styrene acrylate copolymer/	
Copolimero de acrilato de estireno	25085-34-1
Diethylene glycol monoethyl ether/	
Eter de monoethyl de glicol de Diethylene	111-90-0
Maleic anhydride adduct of polypropylene/	
Aducto maleico anhydride de polipropileno	25722-45-6
Tri-butoxyethyl phosphate/	
Fosfato de Tri-butoxyethyl	78-51-3

MAINTENANCE

INSTRUCCIONES PARA SU USO

Comenzar siempre pasando un estropajo seco por el piso. Quitar goma de mascar, rótulos y demás depósitos sucios con una espátula para masilla o con un rascador de manija larga.

INSTRUCCIONES DE USO:

1. **QUITAR** el sellador viejo según las indicaciones rotuladas utilizando un eliminador de Fullpro apropiado.
2. **APLICAR** una mano fina de APPEARANCE® ADMIRE™ utilizando un estropajo limpio.
3. **SECAR:** Calcular un período de secado de 30 a 60 minutos.
4. **APLIQUE** 3-4 capas. Para obtener mejores resultados, permitiendo suficiente tiempo de secado entre cada capa.

MANTENIMIENTO


1. **PASAR** un estropajo seco por el piso. Quitar goma de mascar, rótulos y demás depósitos sucios con un rascador de manija larga o una espátula para masilla.
2. **PASAR** un estropajo húmedo o una frotadora automática utilizando un limpiador de Fullpro, según las indicaciones rotuladas.

Resistencia Contra Resbalones: El coeficiente estático de fricción (James Machine) cubre o excede 0.5, tal como se establece por ASTM Método D2047-82.

ÚNICAMENTE PARA USO INDUSTRIAL

IMPORTANT: zclar con nada que no esté recomendado ya que podría resultar en condiciones perjudiciales y rendimiento pobre. No verter el producto no utilizado en el recipiente original. Todos los pisos son resbaladizos cuando están mojados. Para prevenir caídas, ejercer precaución al trabajar y bloquear el paso con carteles de "Precaución" hasta que el piso esté completamente seco.

MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS



Fuller Commercial Products

One Fuller Way
Great Bend, KS 67530
United States
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com

98655-0615