



# Appearance<sup>®</sup> Admire<sup>™</sup>

Sealer

**FULLPRO**  
FULLER PROFESSIONAL

# Appearance® Admire™

## Sealer

**Appearance® Admire™** is a versatile sealer formulated with a unique blend of acrylic and urethane polymers. Appearance® Admire™ quickly seals porous surfaces and provides a beautiful high-gloss shine. It can be used in a variety of maintenance programs and is responsive when burnished at low or high speeds.

### Repairable:

It will stand up to high speed burnishing and frequent detergent scrubbing.

### Versatile:

Simplifies floor care by providing effective sealing of porous/old floors and providing an above average gloss with a single product.

### Clear Film:

Dries to a clear film and is specifically formulated to not yellow over time.

### Exceptional Gloss:

Improved urethane formula provides "finish"-like gloss and depth compared to traditional sealer/finish formulas.

## USE INFORMATION:

Before applying **Appearance® Admire™** remove old finish and sealer from floor using appropriate Fullpro stripper and following label directions. Can be used on terrazzo, quarry tile, brick, unglazed ceramic, Mexican tile, slate, unpolished marble and all types of resilient flooring.

## PRODUCT SPECIFICATIONS:

pH.....	8.6 ± 0.2
Appearance.....	Opaque White Emulsion
Fragrance.....	Polymeric
Freezing Point.....	About 32°F
% Non-Volatile Solids.....	19.5 ± 0.5
% Total Solids.....	25.4
Solubility in Water.....	Complete
Flash Point.....	> 212°F
Coverage.....	1700 to 2000 sq. ft. per gallon (may vary due to differences in porosity of the surface)
Slip Resistance: Static coefficient of friction (James Machine) meets or exceeds 0.5 as determined by ASTM D2047-82.	

## INGREDIENTS:

Water.....	7732-18-5
Styrene acrylate copolymer.....	25085-34-1
Diethylene glycol monoethyl ether.....	111-90-0
Maleic anhydride adduct of polypropylene.....	25722-45-6
Tri-butoxyethyl phosphate.....	78-51-3

## Fuller Commercial Products

One Fuller Way  
Great Bend, KS 67530  
United States  
CHEMTREC (800) 424-9300  
Emergency (620) 792-1711  
24 hour Emergency (800) 424-9300  
www.fullercommercial.com

986SS-0418

## DIRECTIONS FOR USE:

### INITIAL APPLICATION

1. **REMOVE** old sealer/finish following label directions using an appropriate Fullpro stripper.
2. **APPLY** a thin coat of **Appearance® Admire™** using a clean FullPro finish mop.
3. **DRY:** Allow 30-60 minutes drying time.
4. **APPLY** 3-4 additional coats. For best results allow adequate drying time between coats.

### MAINTENANCE

1. **DUST MOP** the floor using a FullPro dry mop. Remove gum, labels and other attached soils with a long-handled scraper or putty knife.
2. **DAMP MOP OR AUTOSCRUB** using a Fullpro cleaner or maintainer, following the label directions.
3. burnish the floor with a high speed machine and appropriate pad.

## PRODUCT AVAILABILITY:

9861.....	4/1 Gal.
9865.....	1/5 Gal. Pail
98655.....	1/55 Gal. Drum