

DANGER

Harmful if swallowed. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Prevention

Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves. Wear eye/face protection.

Response

If swallowed: Rinse mouth. Do NOT induce vomiting. **If on skin:** Wash with plenty of water. **If inhaled:** Remove person to fresh air and keep comfortable for breathing. **If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see SDS). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.



FULLPRO

FULLER PROFESSIONAL

RAZOR™

Patented, Fast Acting, No-Rinse Stripper



DANGER


See side panel for precautions and first aid.

Net Contents: One Gallon (3.79L)

INGREDIENTS/INGREDIENTES

Water/Agua..... 7732-18-5
Ethylene glycol phenyl ether/
Etilenglicol fenil éter 122-99-6
Monoethanolamine/
Monoetanolamina 141-43-5
2-Butoxyethanol/2-Butoxietanol 111-76-2
Sodium 1-octane sulfonate/
1-Octanosulfonato sódico 5324-84-5

CAS#



00785990098915



Fuller Commercial Products

One Fuller Way
Great Bend, KS 67530
United States
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com

RAZOR™ Patented, Fast Acting, No-Rinse Stripper

Product No.: 9891

RAZOR™ No-Rinse Stripper is a highly active, low foam stripper that quickly penetrates and effectively dissolves multiple layers of floor finish build-up for easy, rinse-free removal. For use on vinyl, vinyl composition, vinyl asbestos, asphalt, marble, terrazzo, concrete and magnesite surfaces.

FLOOR STRIPPING



DIRECTIONS FOR FLOOR CLEANING

Before stripping always dust mop the floor and remove gum, labels and other attached soil deposits with a long handled scraper or utility knife.

FLOOR STRIPPING

- DILUTE** at 21 ounces per gallon (1:6 ratio) of cool water for normal buildup or 32 ounces per gallon (1:4 ratio) of cool water for extreme build up.
- APPLY** the diluted solution of Razor™ onto the floor with a mop.
- WAIT:** Let stand for 4-5 minutes, then agitate with the same mop. For best results use a rotary machine and black pad. Do not let solution dry.
- REMOVE** the solution from the floor using a mop or wet/dry vacuum. For best results rinse the floor with clean water and a clean mop.
- REPEAT** steps two to four if any finish remains on floor.

Special Precautions:

Use caution as floors become very slippery. Must be diluted. Not for use on wood or painted surfaces. Not for use on linoleum or rubber floors or daily maintenance of resilient floors. Before use on asphalt tile, test a small hidden area for any color change.

FOR INDUSTRIAL USE ONLY

IMPORTANT: Use only as directed. Do not mix with anything unless recommended since harmful conditions and poor performance could result. Do not pour unused product back into original container. All floors are slippery when wet. To prevent falls, exercise care when working and block off traffic with "Caution" signs until floor is completely dry.

KEEP OUT OF REACH OF CHILDREN

INSTRUCCIONES PARA SU USO

Antes pelar siempre fregona de polvo el piso y quita goma, las etiquetas y otros depósitos conectados de tierra con un cuchillo de mango largo de raspador o utilidad.

REMOVER

- Diluir** a 21 onzas por galón (1:6 ratio) de agua fría de acumulación normales o 32 oz por galón (1:4 ratio) de agua fresca para la acumulación extrema de hasta.
- APLICAR** la solución diluida de Razor™ sobre el piso con un mapeador.
- ESPERAR:** Permitir de 4-5 minutos, despues revolverlo con el mismo mapeador. Para mejores resultados use la maquina rotatoria con la almohadilla negra. No permita que la solución se seque.
- QUITE** la solución del piso usando un estropajo o una aspiradora de mojado/seco. Para obtener mejores resultados, enjuague el piso con agua limpia y un estropajo limpio.
- REPETIR** los pasos dos al cuatro si aun queda algún remanente del acabado anterior en el piso.

Las PRECAUCIONES ESPECIALES:

Utilice el cuidado como pisos llegan a ser muy resbaladizos. Debe ser diluido. No para uso en la madera ni superficies pintadas. No para uso en el linóleo ni el caucho sola ni la conservación diaria de pisos elásticos. Antes uso en el mosaico de asfalto, prueba una pequeña área escondida para cualquier cambio del color.

ÚNICAMENTE PARA USO INDUSTRIAL

IMPORTANTE: Sólo usar según lo indicado. No mezclar con nada que no esté recomendado ya que podría resultar en condiciones perjudiciales y rendimiento pobre. No verter el producto no utilizado en el recipiente original. Todos los pisos son resbaladizos cuando están majados. Para prevenir caídas, ejercer precaución al trabajar y bloquear el paso con carteles de "Precaución" hasta que el piso esté completamente seco.

MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS

9891-0914