

Razor

Patented, Fast Acting, No-Rinse Stripper





Patented, Fast Acting, No-Rinse Stripper

Razor™ is specially formulated to quickly penetrate and effectively dissolve multiple layers of floor finish buildup for easy rinse-free removal. It can be used on vinyl, vinyl composition, vinyl asbestos, asphalt, marble, terrazzo, concrete and magnesite surfaces.

No Rinsing or Neutralizing:

Rinsing is not required. Pick up the dissolved finish Recommended for use with automatic scrubbers, completely with a wet vac, mop or autoscrubber.

Powerful, Fast Action:

Machine scrubbing is not required. The powerful solvent action of **Razor™** dissolves finish buildup using only mop agitation.

Low Foaming:

low foaming action controls foam in recovery tanks.

Low Odor:

Recommended for use in institutions or other public places where strong odors could be objectionable.

USE INFORMATION:

Hospitals, schools, nursing homes, hotels, motels, schools, universities, municipal buildings, and supermarkets.

PRODUCT SPECIFICATIONS:

pH (concentrate)	13.0 ± 0.3
Appearance	Liquid, Clear to Colorless
Fragrance	Characteristic odor
Freezing Point	About 32°F
Solubility in Water	Complete
Flash Point	None to Boiling

INGREDIENTS:

Water	7732-18-5
Ethylene glycol phenyl ether	122-99-6
Monoethanolamine	141-43-5
2-Butoxyethanol	111-76-2
Sodium 1-octane sulfonate	5324-84-5

DIRECTIONS FOR USE:

Always dust mop floor first. Remove gum, labels and other attached soil deposits with a putty knife or long handled scraper.

FLOOR STRIPPING

- 1. DILUTE at 21 ounces per gallon (1:6 ratio) of cool water for normal buildup or 32 ounces per gallon (1:4 ratio) of cool water for extreme build up.
- 2. APPLY the diluted solution of Razor™ onto the floor with a mop.
- 3. WAIT: Let stand for 4-5 minutes, then agitate with the same mop. For best results use a rotary machine and black pad. Do not let solution dry.
- 4. **REMOVE** the solution from the floor using a mop or wet/dry vacuum. For best results rinse the floor with clean water and a cleanmop.
- 5. **REPEAT** steps two to four if any finish remains on floor.

Special Precautions:

Use caution as floors become very slippery. Must be diluted. Not for use on wood or painted surfaces. Not for use on linoleum or rubber floors or daily maintenance of resilient floors. Before use on asphalt tile, test a small hidden area for any color change.

Fuller Commercial Products

One Fuller Way Great Bend, KS 67530 United States CHEMTREC (800) 424-9300 Emergency (620) 792-1711 24 hour Emergency (800) 424-9300 www.fullercommercial.com

PRODUCT AVAILABILITY:

9891	4/1 Gal.
9895	1/5 Gal. Pail
98955	1/55 Gal. Drum