

FLOOR CARE



DE-FENSE®

Non-Buff Floor Finish

- **Economical**
- **Easy Application**
- **Excellent Gloss**



DE-FENSE®

Non-Buff Floor Finish

DE-FENSE® is a highly detergent resistant, scrubbable, acrylized floor finish that dries to an ultra-dry bright gloss and maintains its exceptional gloss for extended periods of time under heavy traffic conditions. **DE-FENSE®** resists black heel marks and scuffing, and with minimal maintenance, retains its unusually hard durable glossy film. Recommended for offices, schools, healthcare or anywhere a conventional maintenance program is used.

Economical:

The product of choice when quality and value are primary concerns.

Excellent Scuff & Black Heel Mark Resistance:

Unusually hard and glossy characteristics, repairs exceptionally well, when used in conjunction with conventional maintenance systems.

Easy Application:

"Lay down" and leveling ease. A very "forgiving" finish...easy to repair, recoat, and restore.

Dry Bright Finish:

Exceptional "dry bright" characteristics with minimal maintenance. Perfect for schools, health care, public buildings, and municipalities.

USE INFORMATION:

DE-FENSE® can be used on all resilient and non-resilient flooring as well as sealed wood, cork, concrete, terrazzo and "no wax" floors.

PRODUCT SPECIFICATIONS:

pH.....	8.8 ± 0.4
Appearance.....	Off White Emulsion
Fragrance.....	Polymeric
Freezing Point.....	About 32°F
% Total Solids.....	21.8
% Non-Volatile Solids.....	17.0
Boiling Point.....	212°F
Solubility in Water.....	Dispersible
Flash Point.....	None
Coverage.....	1800 to 2200 sq. ft. per gallon (may vary due to differences in porosity of the surface)

SLIP RESISTANCE: Static coefficient of friction (James Machine) meets or exceeds 0.5 as determined by ASTM D2047-82.

INGREDIENTS:

Water.....	7732-18-5
Acrylate copolymers.....	25987-66-0
Diethylene glycol monoethyl ether.....	111-90-0
Ethylene Copolymer.....	67892-91-5
Modified resin polymer.....	Mixture
Tri-butoxyethyl phosphate.....	78-51-3

Franklin Cleaning Technology

One Fuller Way
Great Bend, KS 67530
United States
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com

F1350SS-0318

DIRECTIONS FOR USE:

INITIAL APPLICATION

1. **REMOVE** old sealer or finish using a Franklin stripper and following label directions.
2. **APPLY** a thin coat of **DE-FENSE®** using a clean finish mop and a bucket.
3. **WAIT** 20 to 30 minutes drying time.
4. **APPLY** 2-3 coats. For best results allow adequate drying time between each coat. Buffing is not necessary.

MAINTENANCE

1. **DUST MOP** the floor. Remove gum, labels and other attached soil deposits with a long handled scraper or putty knife.
2. **DAMP MOP OR AUTOSCRUB** using a Franklin cleaner and following the label directions.
3. **SPRAY BUFF** the floor to remove black heel marks, scuffs and scrapes in the finish.

PRODUCT AVAILABILITY:

F135022.....	4/1 Gal.
F135025.....	1/5 Cube
F135038.....	1/55 Drum