

FLOOR CARE



Aurora™

Ultra Gloss Urethane Fortified Finish

- **High Gloss Formula**
- **Versatility**
- **Superb Durability**



Aurora™

Ultra Gloss Urethane Fortified Finish

Aurora™ provides outstanding initial gloss and is urethane fortified for increased resistance to soil penetration, scuffing and black heel marks. **Aurora™** is an excellent choice for high speed and UHS maintenance programs.

Durable:

Exceptional resistance to heel marking, scuffing and repeated scrubbing with detergents. Both stripping and recoating cycles are extended, lowering the frequency of these costly procedures.

High Gloss Formula:

The urethane fortified floor finish emulsion provides the highest level of gloss.

Superior Soil Resistance:

The tough film of **Aurora™** minimizes soil penetration and surface abrasion even under extreme conditions. Autoscrubbing easily picks up dirt, immediately restoring the shine.

Versatility:

Aurora™ is an excellent choice for propane and high-speed burnishing programs and is formulated to be VOC Compliant.

USE INFORMATION:

Recommended on all types of resilient and non-resilient floors which include vinyl composition, rubber, asphalt, quarry, terrazzo and sealed wood floors.

PRODUCT SPECIFICATIONS:

pH.....	8.5 ± 0.5
Appearance.....	Opaque white emulsion
Fragrance.....	Mild polymeric
Freezing Point.....	About 32°F
% Total Solids.....	24.0
% Non-Volatile Solids.....	20.0
Boiling Point.....	212°F
Solubility in Water.....	Dispersible
Flash Point.....	None
Coverage.....	1800 to 2200 sq. ft. per gallon (may vary due to differences in porosity of the surface)

SLIP RESISTANCE: Static coefficient of friction (James Machine) meets or exceeds 0.5 as determined by ASTM D2047-82.

INGREDIENTS:

Water.....	7732-18-5
Styrene acrylic copolymer emulsion.....	Mixture
Diethylene glycol monoethyl ether.....	111-90-0
Tri butoxyethyl phosphate.....	78-51-3
Polyethylene emulsion.....	Mixture

Franklin Cleaning Technology

One Fuller Way
Great Bend, KS 67530
United States
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com

F1370SS-0318

DIRECTIONS FOR USE:

INITIAL APPLICATION

1. **REMOVE** old sealer or finish using an appropriate Franklin stripper and following label directions.
2. **APPLY** a thin, even coat of **Aurora™** using a clean finish mop.
3. **WAIT** 20 to 30 minutes of drying time.
4. **APPLY** 4 coats. For best results allow adequate drying time between each coat. Buffing is not necessary.
5. **BURNISH:** Recommended 24 hours after last coat.

MAINTENANCE

1. **DUST MOP** the floor. Remove gum, labels, and other attached soil deposits with a long-handled scraper or putty knife.
2. **DAMP MOP OR AUTOSCRUB** using Franklin UHS Combo Cleaner/Maintainer and following the label directions.
3. **BURNISH** the floor after cleaning with an ultra high speed or high speed machine using the appropriate pad.

If the floor begins to look worn, an occasional scrub & recoat will decrease the need for frequent stripping.

PRODUCT AVAILABILITY:

F137026..... 1/5 Pail