

FLOOR CARE



Accolade™

Sealer/ Finish

- Versatile
- Excellent Gloss
- Repairable



FRANKLIN
CLEANING TECHNOLOGY

Accolade™

Sealer/ Finish

Accolade™ is a versatile sealer/finish which has been formulated to protect a wide variety of non-resilient and resilient flooring materials. By blending acrylic polymer elements fortified with urethane, Franklin has combined the properties of a top quality sealer with those of a superior floor finish.

Versatility:

Accolade™ simplifies floor care by providing effective sealing of porous/old floors and providing an above average gloss with a single product.

Repairable:

Accolade™ will stand up to high speed burnishing and frequent detergent scrubbing.

Exceptional Gloss:

Accolade™ improved urethane formula provides "finish" like gloss and depth compared to traditional sealer/ finish formulas.

Clear Film:

Accolade™ dries to a clear film and is specifically formulated to not yellow over time.

USE INFORMATION:

Can be used on terrazzo, quarry tile, brick, unglazed ceramic, Mexican tile, slate, unpolished marble and all types of resilient flooring.

PRODUCT SPECIFICATIONS:

pH.....	8.6 ± 0.2
Appearance.....	Opaque White Emulsion
Fragrance.....	Polymeric
Freezing Point.....	About 32°F
% Total Solids.....	25.4
% Non-Volatile Solids.....	19.5 ± 0.5
Boiling Point.....	212°F
Solubility in Water.....	Dispersible
Flash Point.....	None
Coverage.....	1700 to 2000 sq. ft. per gallon (may vary due to differences in porosity of the surface)

SLIP RESISTANCE: Static coefficient of friction (James Machine) meets or exceeds 0.5 as determined by ASTM D2047-82.

INGREDIENTS:

Water.....	7732-18-5
Styrene acrylic polymer.....	25085-34-1
Diethylene glycol monoethyl ether.....	111-90-0
Polypropylene emulsion.....	Mixture
Tri butoxyethyl phosphate.....	78-51-3

Franklin Cleaning Technology

One Fuller Way
Great Bend, KS 67530
United States
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com

F1390SS-0318

DIRECTIONS FOR USE:

INITIAL APPLICATION

1. **REMOVE** old sealer/finish following label directions using an appropriate Franklin stripper.
2. **APPLY** a thin coat of **Accolade™** using a clean finish mop.
3. **DRY:** Allow 30-60 minutes drying time.
4. **APPLY** 3-4 additional coats. For best results allow adequate drying time between coats.

MAINTENANCE

1. **DUST MOP** the floor. Remove gum, labels and other attached soils with a long-handled scraper or putty knife.
2. **DAMP MOP OR AUTOSCRUB** using a Franklin cleaner, following the label directions.

PRODUCT AVAILABILITY:

F139022.....	4/1 Gal.
F139026.....	1/5 Pail
F139038.....	1/55 Drum