

FLOOR CARE



Restorit®

UHS Maintainer / Spray Buff

- Rejuvenates Finish Gloss
- Prolongs Finish Life
- Saves Labor



Restorit®

UHS Maintainer / Spray Buff

Restorit® is a multi-purpose floor finish maintainer designed for high speed maintenance programs. It may be used with a mop and bucket, with an autoscrubber, or as a spray buff. Restorit® rejuvenates the finish to produce the wet look and prolongs the life of your finish.

Maintains A Wet Look Gloss:

Prolongs the finish's life when applied regularly after cleaning.

Easy To Apply:

The finish is restored as easy as damp mopping, autoscrubbing, or spray buff application.

Multiple Use:

Use as a mop-on restorer as a cleaner in the autoscrubber, or as a spray buff.

"Pops" The Gloss:

The finish gleams after high speed buffing.

USE INFORMATION:

Always dust mop floor first. Remove gum, labels and other attached soil deposits with a putty knife or long handled scraper. For best results preclean the floor with Franklin Compare™.

PRODUCT SPECIFICATIONS:

pH (concentrate).....	9.5 ± 0.5
Appearance.....	Milky Light Green
Fragrance.....	Polymeric
Solids.....	7.3 ± 0.2
Freezing Point.....	About 32°F
Solubility in Water.....	Complete
Flash Point.....	None
Coverage.....	4000 to 20000 sq. ft. per gallon (may vary due to differences in porosity of the surface)

SLIP RESISTANCE: Static coefficient of friction (James Machine) meets or exceeds 0.5 as determined by ASTM D2047-82.

INGREDIENTS:

Water.....	7732-18-5
Acrylate copolymer.....	25987-66-0
Diethylene glycol monoethyl ether.....	111-90-0
Modified melamine resin.....	68002-20-0
Ethylene glycol.....	107-21-1

DIRECTIONS FOR USE:

AUTOSCRUB APPLICATION

1. **DILUTE Restorit®** at 6 ounces per gallon (1:20 ratio) of cool water in the solution tank.
2. **AUTOSCRUB:** Apply solution and scrub with a red or white pad. Squeegee up excess solution from the floor and allow to dry thoroughly.
3. **BURNISH** as desired to "pop-the-gloss".

MOP-ON APPLICATION

1. **DILUTE Restorit®** at 32 ounces per gallon (1:4 ratio) of cool water.
2. **APPLY** solution with a clean mop. Change solution when it becomes dirty. No rinsing required. Allow to dry thoroughly.
3. **BURNISH** as desired to "pop-the-gloss".

SPRAY BUFF APPLICATION

1. **SPRAY** undiluted product onto a 4' x 6' area using a fine to medium spray. If using ultra high-speed equipment, spray sparingly in front of machine.
2. **BUFF** to a shine using a low speed rotary machine with a red or white polishing pad. With ultra high-speed equipment, use an appropriate burnishing pad.

PRODUCT AVAILABILITY:

F191022..... 4/1 Gal.

Franklin Cleaning Technology

One Fuller Way
Great Bend, KS 67530
United States
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com

F1910SS-0318