

Side Out

GYM FLOOR FINISH

DATA TECH SHEET

PRODUCT DESCRIPTION:

Side Out is an acrylic wood floor finish that provides a highly durable coating with extremely high gloss in gymnasiums, sports floors and other wood surface floors. Easy to apply. Dries quick. Repels scratching, scuffing and rubber burn marks. Recommended to be used on sealed wood floors.

FEATURES:

Advantages:

- Excellent gloss
- Superior Hardness
- Non-yellowing
- Excellent rubber burn resistance
- Dries quickly under normal conditions
- Burnishable

Balance of Performance:

Provides outstanding durability and excellent abrasion and chemical resistance in heavy traffic environments.

PRODUCT SPECIFICATIONS:

pH	8.5 ± 0.5
Appearance	Off White Liquid
Fragrance	Polymeric
Freezing Point	About 32°F
% Solids	30%
Boiling Point	212°F
Solubility in Water	Dispersible
Flash Point	None
Coverage500 to 700 sq. ft. per gallon

(may vary due to differences in porosity of the surface)

Slip Resistance: Static coefficient of friction (James Machine) meets or exceeds 0.5 as determined by ASTM D2047-82.

INGREDIENTS:

Water	7732-18-5
Acrylic polymer	Mixture
Diethylene glycol monoethyl ether	111-90-0
Dibutyl phthalate	84-74-2
Oxidized polyethylene wax	68441-17-8

DILUTIONS	HEALTH	FLAMMABILITY	REACTIVITY
CONCENTRATE	NFPA 0 H315	NFPA 0 H228	NFPA 0 H314
CONCENTRAR	SALUD	INFLAMABILIDAD	REACTIVIDAD

0	1	2	3	4
Minimal	Slight	Moderate	Serious	Severe
Mínimo	Mínimo	Moderar	Grave	Drástico

SIDE OUT GYM FLOOR FINISH

DIRECTIONS

USE INFORMATION

Designed to be used on wood sports floors in public and private schools, universities, professional arenas, and health clubs. Can also be used on private wood flooring following use directions.

NOTE: Avoid applying on extremely hot and humid days or when floor temperature is below 21°C.
NOTE: Wet floors are slippery. Prevent pedestrian traffic with a wet floor sign or barricades.

APPLICATION

1. Remove all soil. Wear non-marking soft-soled gym shoes. Check for wax, gum or other substances.
2. Screen entire floor with 120-150 grit screens until floor is uniformly dull. Remove any swirls caused by screens with sequential "fine" screens (above 150 grit).
NOTE: For scrub and recoat procedure scrub floor using an auto scrubber or swing machine with a brown, black or surface prep pad depending on condition of floor. Follow all other procedures as described.
3. Before tacking, be sure doors are locked and air movement (fan) is turned off.
4. Sweep and vacuum up all dust from floor. Do not use treated dust mops. Floor dust is combustible. Remove from vacuums and all containers.
5. Tack floor with WATER-DAMPENED turkish towels, tightly wrung out. Repeat tacking until floor is dust free.
6. Allow floor to dry until there is NO sign of moisture.
7. Apply first coat using a **light weight** t-bar applicator. Work steadily without stopping, feathering as you go, until the entire coat is applied.
8. Allow to dry (2-4 hours under normal conditions). Do not exceed 16 hours prior to recoating or screening or scrubbing will be necessary.
9. Apply second coat using same method as above.
10. If additional gloss is desired, apply a third coat as in step #7.
11. Release to light traffic after 24 hours and heavy traffic after 48 hours.

DANGER

May damage fertility or the unborn child. May cause mild eye and skin irritation. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Prevention

Obtain special instructions before use (see SDS). Do not handle until all safety precautions have been read and understood. Avoid release to the environment. Wear protective gloves / protective clothing / eye protection / face protection.

Response

If exposed or concerned: Get medical advice / attention.

Storage

Store locked up.

Disposal

Dispose of contents/container in accordance with local / regional / national / international regulations.



WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Franklin Cleaning Technology

One Fuller Way
Great Bend, KS 67530
United States
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com

PERSONAL PROTECTION:

Respiratory Protection: Not needed in normal use of this product.

Ventilation: Use with adequate ventilation.

Eye Protection: Safety glasses are recommended.

Protective Gloves: Protective gloves are recommended.

Other Protective Clothing or Equipment: Wear clothing as necessary to prevent skin contact.

TRANSPORTATION

INFORMATION:

U.S. DOT - Proper Shipping

Name: Not regulated by DOT.

Marine Pollutant: No