

FLOOR CARE



Super Gard™

Undercoater Sealer

- **Blocks Stains**
- **Non-Yellowing**
- **Easy, Economical Protection**



Super Gard™

Undercoater Sealer

Super Gard™ represents a "modern concept" in acrylized emulsion polymer chemistry. It is a major breakthrough in reference to the total undercoater/sealer protection of all resilient and non-resilient floors, with the exception of unsealed wood floors. Super Gard™ is formulated with metalized acrylic polymers, thereby achieving exceptional levels of durability and protection. Super Gard™ is an excellent choice where protection from salt exposure is required.

Super Protective Coating:

Super Gard™ is salt resistant and has outstanding black heel mark and scuff resistance properties.

Exceptional Stain Resistance:

Super Gard™ prevents stains from setting into the floor. The floor is protected from oil, rust, betadine and other soils.

Non-Yellowing:

Super Gard™ is a water-based system with no waxes or resins to cause darkening or yellowing.

Easy and Economical:

No foaming or streaking even under high humidity conditions. Increases the coverage of top coating.

USE INFORMATION:

Super Gard™ is recommended for use on vinyl composition, vinyl asbestos, vinyl, asphalt, linoleum and rubber floors. May be used on nonresilient surfaces that are not glazed. These surfaces include concrete, terrazzo, quarry tile, Mexican tile, brick, marble, slate and other nonresilient floors.

PRODUCT SPECIFICATIONS:

pH.....	8.8 ± 0.5
Appearance.....	White Emulsion
Fragrance.....	Polymeric
Freezing Point.....	About 32°F
% Total Solids.....	21.1
% Non-Volatile Solids.....	16.3
Boiling Point.....	212°F
Solubility in Water.....	Complete
Flash Point.....	None
Coverage.....	1700 to 2000 sq. ft. per gallon (may vary due to differences in porosity of the surface)

SLIP RESISTANCE: Static coefficient of friction (James Machine) meets or exceeds 0.5 as determined by ASTM D2047-82.

INGREDIENTS:

Water.....	7732-18-5
Acrylatecopolymer.....	28263-96-9
Ethylene glycol.....	107-21-1
Diethylene glycol monoethyl ether.....	111-90-0
Tri butoxyethyl phosphate.....	78-51-3

Franklin Cleaning Technology

One Fuller Way
Great Bend, KS 67530
United States
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 hour Emergency (800) 424-9300
www.fullercommercial.com

F3160SS-0318

DIRECTIONS FOR USE:

INITIAL APPLICATION

1. **REMOVE** old sealer or finish using a Franklin stripper and following label directions.
2. **APPLY** one or two coats of **Super Gard™** using a clean finish mop and a bucket.
3. **DRY:** For best results allow adequate drying time between each coat.
4. **FINISH:** Apply 2-3 additional coats of a Franklin floor finish. For best results allow adequate drying time between each coat.

MAINTENANCE

1. **DUST MOP** the floor. Remove gum, labels and other attached soils with a long-handled scraper or putty knife.
2. **DAMP MOP OR AUTOSCRUB** using a Franklin cleaner, following the label directions.

PRODUCT AVAILABILITY:

F316026.....	1/5 Pail
F316038.....	1/55 Drum